

KITCHEN DISPLAY SYSTEMS

Proven. Reliable.



Increase kitchen throughput with PAR EverServ®KDS solutions, used with PAR Brink POS Application Software.

The KDS Controller fan-less design is quiet, offers low power consumption and minimizes maintenance. The Bump Bar offers a spill resistant, high-impact enclosure that is built to withstand tough restaurant conditions with continuous operation. Both units have secure, versatile mounting options with cable management.

KDS Controller*



*Compatible with Brink Software only

Highlights

Preinstalled Win 8.1 Industry Pro Retail
Intel Baytrail J1900 2.41GHz CPU
Fanless Design
3 Serial Ports, 1 USB 3.0
1 Gigabit LAN, 1 VGA Power, 1 Display Port
Small Form Factor
VESA 100mmx100mm Mounting
Optional 802.11b/g/n Wireless

Size, Weight & Environmental

Height: 1.4 inches (3.68cm)
Width: 5.4 inches (13.8cm)
Depth: 8.7 inches (22.2cm)
Weight: 2.6 lbs. (1.2kg)
Operating Temperature: 0C to 35C
Humidity: 20-85% (Non-condensing)

KDS Bump Bar




Highlights

Logic Controls KB1700
17 Programmable tactile keys
Switches rated at 3 million cycles
UV-resistant high durability casing
Internal beeper
Windows-base utility included
Versatile Mounting

Size, Weight & Environmental

Height: 3.5 inches (8.89cm)
Width: 9.25 inches (23.5cm)
Depth: 1.13 inches (2.87cm)
Weight: 0.70 lbs. (0.45kg)
Temperature: 32-122°F (0-50°C)
Humidity: 15-85% (Non-condensing)

CONTACT **PAR** FOR MORE INFORMATION

 8383 Seneca Turnpike, New Hartford, NY 13413
(800) 533.2118 | www.partech.com